



Model 1: 1000 kg

The 1000 kg model is a compact, single-engine machine designed for small-scale construction work. It features a single front wheel and a rear wheel, with a compact body and a single operator's seat. The machine is designed for easy maneuverability and is suitable for tasks such as light grading, trenching, and backfilling.



Model 2: 1500 kg

The 1500 kg model is a more powerful machine, designed for medium-scale construction work. It features a single front wheel and a rear wheel, with a more robust body and a single operator's seat. The machine is designed for easy maneuverability and is suitable for tasks such as light grading, trenching, and backfilling.

The 1500 kg model is a more powerful machine, designed for medium-scale construction work. It features a single front wheel and a rear wheel, with a more robust body and a single operator's seat. The machine is designed for easy maneuverability and is suitable for tasks such as light grading, trenching, and backfilling.

Model	Weight (kg)	Engine Power (kW)	Max. Speed (km/h)	Max. Trench Depth (mm)	Max. Backfill Depth (mm)
Model 1	1000	15	10	100	100
Model 2	1500	25	15	150	150
Model 3	2000	35	20	200	200
Model 4	2500	45	25	250	250
Model 5	3000	55	30	300	300
Model 6	3500	65	35	350	350
Model 7	4000	75	40	400	400
Model 8	4500	85	45	450	450
Model 9	5000	95	50	500	500
Model 10	5500	105	55	550	550

Model 3: 2000 kg

The 2000 kg model is a more powerful machine, designed for medium-scale construction work. It features a single front wheel and a rear wheel, with a more robust body and a single operator's seat. The machine is designed for easy maneuverability and is suitable for tasks such as light grading, trenching, and backfilling.



Model 4: 2500 kg

The 2500 kg model is a more powerful machine, designed for medium-scale construction work. It features a single front wheel and a rear wheel, with a more robust body and a single operator's seat. The machine is designed for easy maneuverability and is suitable for tasks such as light grading, trenching, and backfilling.

The 2500 kg model is a more powerful machine, designed for medium-scale construction work. It features a single front wheel and a rear wheel, with a more robust body and a single operator's seat. The machine is designed for easy maneuverability and is suitable for tasks such as light grading, trenching, and backfilling.

Model	Weight (kg)	Engine Power (kW)	Max. Speed (km/h)	Max. Trench Depth (mm)	Max. Backfill Depth (mm)
Model 1	1000	15	10	100	100
Model 2	1500	25	15	150	150
Model 3	2000	35	20	200	200
Model 4	2500	45	25	250	250
Model 5	3000	55	30	300	300
Model 6	3500	65	35	350	350
Model 7	4000	75	40	400	400
Model 8	4500	85	45	450	450
Model 9	5000	95	50	500	500
Model 10	5500	105	55	550	550

Hand Protection
 The gloves must be suitable for the task and the environment. They must be worn correctly and for the full duration of the task. They must be replaced if they become damaged or contaminated.



Hand Protection
 The gloves must be suitable for the task and the environment. They must be worn correctly and for the full duration of the task. They must be replaced if they become damaged or contaminated.



Foot Protection
 The footwear must be suitable for the task and the environment. It must be worn correctly and for the full duration of the task. It must be replaced if it becomes damaged or contaminated.



Foot Protection
 The footwear must be suitable for the task and the environment. It must be worn correctly and for the full duration of the task. It must be replaced if it becomes damaged or contaminated.



Head Protection
 The headgear must be suitable for the task and the environment. It must be worn correctly and for the full duration of the task. It must be replaced if it becomes damaged or contaminated.



Head Protection
 The headgear must be suitable for the task and the environment. It must be worn correctly and for the full duration of the task. It must be replaced if it becomes damaged or contaminated.



Eye Protection
 The eye protection must be suitable for the task and the environment. It must be worn correctly and for the full duration of the task. It must be replaced if it becomes damaged or contaminated.



Eye Protection
 The eye protection must be suitable for the task and the environment. It must be worn correctly and for the full duration of the task. It must be replaced if it becomes damaged or contaminated.

